

\*\*\*\*\***MATERIAL SAFETY DATA SHEET**\*\*\*\*\*

Manufacturer's Name: NOVA INDUSTRIES, LLC  
Street Address: 8011 No. 154 East Avenue  
City, State, Zip: Owasso, OK 74055  
Phone: (918)230-5826 Fax: (918) 437-3164

\*\*\*\*\***SECTION I – PRODUCT IDENTIFICATION**\*\*\*\*\*

CHEMICAL FAMILY:  
CHEMICAL NAME OR SYNONYM: Aqueous Acrylic Emulsion  
FORMULA: The specific chemical formula for this material is a Trade Secret of  
SPEEDLINER L.L.C.

\*\*\*\*\***SECTION II – INGREDIENTS**\*\*\*\*\*

<u>WEIGHT %</u>	<u>TWA/TLV</u>
-----------------	----------------

ACRYLIC POLYMER: 53-57	Not established
RESIDUAL MONOMERS (see Section X):	Trace
AMMONIA: 0.2max	25ppm (ACGIH)
WATER: 43-47	

\*\*\*\*\***SECTION III – PHYSICAL DATA**\*\*\*\*\*

APPEARANCE: Milky-white liquid  
ODOR: Mild ammoniacal  
pH: 9-10  
VISCOSITY: 15,000 cps max  
MELTING/FREEZING POINT: OC/32 F water  
BOILING POINT: 100 C/212 F water  
VAPOR PRESSURE (mm/Hg): 17 20 C/68 F  
VAPOR DENSITY (air =1): 1 water  
SOLUBILITY IN WATER: Dilutable  
% VOLATILE (by weight): 43-47 water  
SPECIFIC GRAVITY (water = 1): 1-1.2  
EVAPORATION RATE (Butyl Acetate = 1): 1 water

\*\*\*\*\*SECTION IV – FIRE AND EXPLOSION HAZARD DATA\*\*\*\*\*

FLASH POINT: Non-combustible  
AUTO IGNITION TEMPERATURE: N/A  
LOWER EXPLOSION LIMIT (%): N/A  
UPPER EXPLOSION LIMIT (%): N/A  
SPECIAL FIRE FIGHTING PROCEDURES: N/A  
UNUSUAL FIRE AND EXPLOSION HAZRDS: Material can splatter above 100 C (212 F). Polymer film can burn above 1200 C.

\*\*\*\*\*SECTION V – HEALTH HAZARD DATA\*\*\*\*\*

Recommended Health Guide TWA (maximum time-weighted-average concentration for 8-hour work period).

AMMONIA: 25 ppm  
EFFECTS OF OVEREXPOSURE WHEN SPRAYING:  
INHALATION: Vapor or spray mist can cause headache, nausea and irritation of the nose, throat and lungs.  
SKIN CONTACT: Slightly irritating to skin.  
EYE CONTACT: Possibly irritating to eyes.  
EMERGENCY FIRST AID PROCEDURES:  
INHALATION: Move subject to fresh air.  
EYE CONTACT: Flush eyes with a large amount of water for at least 15 minutes. See physician if irritation persists.  
SKIN CONTACT: Wash affected skin area with soap and water.

\*\*\*\*\*SECTION VI – REACTIVITY DATA\*\*\*\*\*

STABILITY: Stable  
CONDITIONS TO AVOID: N/A  
HAZARDOUS DECOMPOSITION PRODUCTS: N/A  
HAZARDOUS POLYMERIZATION: Will not occur  
INCOMPATIBILITY MATERIALS TO AVOID: N/A

\*\*\*\*\*SECTION VII – SPILL OR LEAK PROCEDURE\*\*\*\*\*

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Floor may be slippery, use care to avoid falling. Dike may contain spill with inert material, e.g., sand, earth. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

(continued)

WASTE DISPOSAL METHODS: Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant liquid and flush to a chemical sewer. Landfill the solids and the contaminated diking material according to local, state, and federal regulations.

\*\*\*\*\***SECTION VIII – SPECIAL PROTECTION INFORMATION**\*\*\*\*\*

VENTILATION TYPE: Mechanical local exhaust ventilation at point of contaminant release.

RESPIRATORY PROTECTION: None required when permissible airborne concentrations are not exceeded.

PROTECTIVE GLOVES: Impervious

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or approved equivalent).

OTHER PROTECTIVE EQUIPMENT: N/A

\*\*\*\*\***SECTION IX – STORAGE AND LABELING**\*\*\*\*\*

STORAGE TEMPERATURE: 60 C/140 F max. 1 C/34 F min.

PRECAUTIONARY LABELING: KEEP FROM FREEZING - PRODUCT STABILITY MAY BE AFFECTED.

\*\*\*\*\***SECTION X – TOXICITY INFORMATION**\*\*\*\*\*

\*\*\*\*\***SECTION XI – TRANSPORTATION INFORMATION**\*\*\*\*\*

This material is not regulated as a DOT hazardous material.

---

TECHNICAL SHIPPING NAME: Water Base Latex Paint

DOT (DOMESTIC SURFACE)

---

PROPER SHIPPING NAME: Liquid Resin (Non-regulated)

HAZARD CLASS OR DIVISION: None

UN/NA NUMBER: None

FREIGHT CLASS: 55

PACKAGING GROUP: None

HAZARDOUS SUBSTANCE: None

DOT PRODUCT RQ lbs.: None

(continued)

\*\*\*\*\***SECTION XII – MISCELLANEOUS INFORMATION**\*\*\*\*\*

**NOTE:** Under normal handling conditions the risk of exposure to residual monomer is negligible. Monomer vapors can be generated, however, when product is heated during processing operations. Maintain adequate ventilation where product is heated or cured. DO NOT inhale spray from product; use respirator if engineering controls are not adequate to main mist, vapor or dust concentrations of acrylic polymer at less than 109 g/m3.

ENVIROLINER IS A TRADEMARK OF SPEEDLINER L.L.C.

N/A – Not applicable                      C – Ceiling Value

The information contained herein is based on data considered to be accurate; however, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the Safety Data Sheet. Additional vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk of his use of the material.